



1127-2

1100 SERIES STRAP-ON STYLE TEMPERATURE CONTROLS

Attach directly to surface of pipe. For use as high limit, reverse acting or SPDT switching action control.

FEATURES

- Hydraulic action element can be mounted in any position - no leveling required
- Dustproof steel case
- Special screw terminals with "ears" securely hold solid and stranded wires
- Includes pipe strap and mounting screws

SPECIFICATIONS


Dimensions 6.88"H (includes plate) X 2.32"W X 3.19"D
 Finish..... Grey
 UL/CUL File NumberE12615

SPDT CONTACT STRUCTURE

HH Rated Controls

SWITCH ACTION

R-B Open on Rise
 R-W Close on Rise



1100 SERIES STRAP-ON STYLE TEMPERATURE CONTROLS

RANGE	DIFFERENTIAL	SWITCH ACTION	MOTOR RATING (FULL LOAD) 120 VAC	MOTOR RATING (FULL LOAD) 240 VAC	VALVES AND RELAYS 24 VAC	VALVES AND RELAYS 0.3-12 VDC	MODEL NUMBER	ITEM NUMBER
100 to 240°F (38 to 116°C)	Fixed 10°F (5.5°C)	SPDT	7.4A	3.7A	2.9A	—	1127-2 ①	11 27 002S1

① Has U.L. approved adjustable dial stop, factory set at 150°F maximum. See White-Rodgers General Information for full electrical ratings.