# White-Rodgers 80 Series™

# Single Stage





### **Single Stage Thermostats**

- 5/1/1 Day, 5/2 Day Programmable or Non-Programmable
- · Hardwired or Battery Powered

## 1F80-0471 Blue

Single Stage 5/1/1, 5/2 Day or 0 Programs Includes Wall Plate F61-2634

## 1F86-0471 Blue

Single Stage **Non-Programmable** 

1F80-361

Single Stage 5/1/1 Day Programmable

1F87-361

Single Stage
7 Day Programmable

1F86-344

Single Stage
Non-Programmable





### 80 Series Adds "Blue" to the Line-Up

The best-selling digital thermostat series now has Blue. 80 Series Blue has a large 4-square-inch, easy-to-view Blue display and enhanced home comfort features. Take all the best features of the 80 Series, add exclusive CoolSavings™, dedicated programmable or non-programmable, longer battery life with exclusive battery power monitor — put it all in a sleek, compact package and you have 80 Series Blue. Tried and true now comes in Blue!





# White-Rodgers

# OD Series™ Single Stage Thermostats

7 Day Programmable

#### **Exclusive 80 Series Blue Features**

Large, 4-square-inch Blue display with easy-to-see characters

Configures as manual heat/cool, auto changeover, heat only or cool only

Exclusive Cool Savings™ feature saves energy during peak A/C demand periods

Hydronic 2 or 3 wire applications

Three anticipation settings

Exclusive battery power monitor

Longer battery life

Easy access battery compartment

5-year warranty

#### **Programming**

Choice of 5/1/1 day programmable, 5/2 day or non-programmable (1F80-0471)

Choice of 5/1/1 day (1F80-361) or 7 day programmable (1F87-361)

4 time and 4 temperature settings per program (heat & cool)

Energy savings up to 33%

Patented pre-programmed software simplifies time and temperature programming

#### Display

Large LCD with improved contrast for easier reading

Lighted display for easier low-light viewing

#### Comfort & Convenience

Permanent program retention during power loss

Indefinite setpoint Hold or programmable timed Hold up to 8 hours (1F80-0471) / (1F80-361) / (1F87-361)

Air filter change indicator (optional)

Simple "set-up" menu to activate optional features

Temporary temperature override until next program period (1F80-0471) / (1F80-361) / (1F87-361)

Soft-touch keypad

Maintains room temperature differential within 1°

Display temperature recalibration (+/- 4°)

#### Performance

Dual-Powered...choice of battery-powered or hardwired, for all applications

Selectable Energy Management Recovery (1F80-0471) / (1F80-361) / (1F87-361)

Meets ENERGY STAR® specifications (1F80-0471) / (1F80-361) / (1F87-361)

Meets California Building Code, Title 24 (1F80-0471) / (1F80-361) / (1F87-361)

Fast (FA) or slow (SL) heating cycle anticipation

Easy-to-wire terminal block

Compressor lockout protection

Millivolt compatible

Electric heat option

**Terminal Designations** 

80 Series



























#### **Dimensions**

4.5"W x 3 .5"H x 1.1"D - 80 Series Blue 6.1"W x 3 .8"H x 1.2"D - 80 Series

#### **Electrical Specifications**

Rating

0 to 30 VAC, 50/60 Hz or DC 0.05 to 1.0 Amp (load per terminal)

1.5 Amps maximum load (all terminals combined)

Standard Systems Single Stage gas, oil, electric

Single Stage heat pump

Millivolt Systems

#### Thermal Specifications

Setpoint Temperature Range: 45° to 90° F (7° to 32° C)

80 Series Blue Rated Differential: 0.4° to 1.7° F with adjustable anticipation

80 Series Rated Differential: 0.6° to 1.5° F with adjustable anticipation

**Operating Ambient Temperature:** 32° to 105° F (0° to 40° C)

Operating Humidity Range: 90% non-condensing maximum

**Shipping Temperature Range:** -4° to 150° F (-20° to 65° C)

Accessories

Wall Plate F61-2634 (6.5"W x 5"H) for 80 Series Blue (Included with 1F80-0471)

Wall Plate F61-2500 (7.6"W x 4.8"H) for 80 Series

Thermostat Guard F29-0231

(For additional guard options refer to White-Rodgers catalog at www.white-rodgers.com)

#### For Additional Information

Visit www.white-rodgers.com

Stages Heat/Cool by System		Programs	Model	Applications				Selectable Performance Features					Comfort & Convenience Features							
Single Stage	Multi- Stage	Heat Pump	Program Options	Model Number	Gas/Oil/ Electric	3 Wire Zone Valve	Millivolt Compatible	Thermostat Power Source*	Auto Changeover	Heat Only or Cool Only Option	Energy Management Recovery	Programmable Fan	Energy Star	Diplay Size (sq. in.)	Alkaline Battery Life (Years)	Lighted Display	Cool Savings	Furnace Lockout Ignition Module Reset	Memory Back-up P-Permanent B-Battery	Warranty (Years)
1/1		1/1	7-day	1F87-361	1		1	B, H			1		1	2.2	2+	1		1	Р	1
1/1		1/1	5+1+1, 5+2, Ø	1F80-0471	1	1	1	В, Н	1	1	1		1	4.0	2+	<b>√</b> **	1	1	Р	5
1/1		1/1	5+1+1	1F80-361‡	1		1	B, H			1		1	2.2	2+	1		/	Р	1
1/1		1/1	Ø	1F86-0471	1	1	1	B, H	1	1				4.0	2+	<b>√</b> **	1	/	Р	5
1/1		1/1	ø	1F86-344‡	1		1	B, H						2.2	2+	1		/	Р	1



B, H = Battery or Hardwire option
 Optional Continuous Display Light with Hardwire Connection
 Hardwire Only Powered Models Also Available

