

# Ionization Smoke & Fire Alarm

## 120 Volt AC Hardwired with Battery Backup

### Model 5304



Perfect for new or replacement installations, this 120 volt AC/DC hardwired smoke and fire alarm

#### Features

- Quick Find® alarm origination feature
- Quick activation battery pull tab
- Universal mounting bracket
- Quick connect wiring harness
- Larger mounting base
- Interconnectable
- Front-load battery drawer
- Single silence/test button
- Full-size plastic dust cover
- 2 tamper resistant locking features
- 10-year alarm warranty

#### Benefits

- Patented feature easily identifies first alarm to sound in an interconnected system
- Preserve battery life. Preinstalled battery is quickly activated without removing alarm from bracket
- Fits any standard wiring junction box, single gang, round or octagon, up to 4"
- Longer 8" pigtail wires are pre-stripped
- Covers drywall imperfections and old paint marks
- With all USI and Universal brand 120V alarm using existing wiring & mounting
- Replace battery without removing alarm from bracket
- Temporarily quiets nonemergency alarms and tests alarm functionality
- Protects alarm from dust, debris and painting during construction or home remodeling
- Prevents unauthorized alarm and battery removal
- 10 years from the date of installation

#### Technical Specifications

Sensor Type:	Dual Ionization Sensing Chamber
Primary Power:	120 Volt AC 60Hz
Battery Backup:	9 Volt super heavy duty battery
Audible Alarm:	85 dB at 10 feet
Temperature Range:	40° F to 100° F (4° C to 38° C)
Humidity Range:	5% to 95% RH
Interconnect:	Maximum 24 USI/Universal devices
LED:	Green=AC power, Red=alarm
Size:	5.63" x 5.63" x 1.75"
Warranty:	10 year limited

#### Regulatory Compliance:

- Underwriters Laboratories (UL-US)
- Underwriters Laboratories Canada (ULC)
- California State Fire Marshal (CSFM)
- National Fire Protection Association (NFPA)
- Housing and Urban Development (HUD)
- Federal Housing Authority (FHA)
- UTGT / UTHA



MODEL	BRAND	Box Clam	QTY	SHELF PACK (in.) L x W x H	WEIGHT (Lbs.)	UPC CODE	QTY	MASTER CTN (in.) L x W x H	WEIGHT (Lbs.)	I2 of 5
5304	USI	BX	1	5.75 x 5.75 x 1.75	0.42	0-42741-05304-4	12	12.00 x 12.00 x 6.13	8.55	1-00-42741-05304-1