

## HPSR10\*

### HONEYWELL HYDRONIC PRO CONTROLLER

#### SUBMITTAL SHEET

Job Name	
Engineer	
Mechanical Contractor	
Contractor's P.O. No.	
Representative	
Notes	

Model(s)				
HPSR101	Qty.		Notes	
HPSR103	Qty.		Notes	
HPSR104	Qty.		Notes	
HPSR106	Qty.		Notes	
Approval				
Service				
Tag No.				



#### APPLICATION

Honeywell's Hydronic Switching Relays are the new standard for Hydronic controls, providing simplified setup and wiring for quick installation.

#### FEATURES

- Familiar Setup
- Flexible mounting
- Color coded wiring and terminals
- Simple layout cover
- Hinged door
- Integrated and visible LED panel
- Works with power stealing stats without the need of an additional resistor
- Auto-resettable fuses as well as backup glass fuses for double protection
- High output transformers for more power
- 5-year warranty

#### INCLUDED IN THE BOX

- Zoning Panel
- Mounting Hardware (3 Screws and 3 Wall Anchors)
- 2, 2-Amp Fuses
- Spare Status Label (French)
- Install Manuals (English & French)

#### SPECIFICATIONS

Model	Zones	Transformers	Input Power	Maximum Combined Load	Pump Fuse	Priority Zone Control	Type 1 Enclosure		
							Width	Height	Depth
HPSR101	1	1	120/60/1 VAC	15 amps	6 Amp	No	5-1/8"	6-3/4"	2-3/8"
HPSR103	3	1	120/60/1 VAC	15 amps	6 Amp	Yes	11-3/4"	8-3/4"	2-1/8"
HPSR104	4	1	120/60/1 VAC	20 amps	6 Amp	Yes	11-3/4"	8-3/4"	2-1/8"
HPSR106	6	1	120/60/1 VAC	20 amps	6 Amp	Yes	11-3/4"	8-3/4"	2-1/8"

Notes:

- All circulator relay connections, including ZC/ZR, are rated 1/3 hp (6FLA, 36LRA) at 120 VAC.
- End switch connections are rated 24 VAC, 1 amp.
- All thermostat connections supply a 24 VAC class 2 output.

#### Home and Building Technologies

In the U.S.:  
Honeywell.  
715 Peachtree Street NE  
Atlanta, GA 30308  
customer.honeywell.com

© U.S. Registered Trademark  
© 2018 Honeywell International Inc.  
33-00380-01 M.S. 05-18  
Printed in United States



33-00380-01