
ZD-XXXX SERIES ZONE CONTROL DAMPER SPECIFICATIONS



APPLICATION:

The model ZD-XXXX is a rectangular commercial zone control damper assembly that includes a 24 Volt, floating point actuator, duct temperature sensor, and actuator control board. The ZD-XXXX zone damper is used as part of a Zone One™ or Z-2000 Comfort System™ when used with a Z-2000-T zone thermostat.

AVAILABLE SIZES:

Side mount models are sized width (A) by height (B) with actuator on the (B) dimension. Bottom mount models are sized width (A) by height (B) with actuator on the (A) dimension. (A) and (B) dimensions are undercut 1/4".

Standard sizes range from 8" x 8" up to 36" x 24" in 2" increments.

CONSTRUCTION:

Frame: 1/16" extruded aluminum

Blades: 1/16" extruded aluminum (parallel design)

Flange: 1/16" aluminum Shaft: ½" aluminum Bushings: Nylon

AIR FLOW & PRESSURE:

Max static pressure:2 inches w.c.Max velocity:2,000 fpmCFM:0 - 4000 cfm

DAMPER ACTUATOR:

FP45-MOTOR

24 VAC, 2.5VA, 3-wire floating point actuator, 45 in-lb, 90 second

timing, 90° stroke

OPERATION:

Continually regulates supply air volume in response to Z-2000-T

thermostat control

COMPONENTS:

Damper, actuator, PC board and discharge air sensor

AIR HANDLER:

Space thermostat or Z-2000 Comfort System™ zone control panel

WARRANTY:

5 Years

Drawings are intended to show general, overall product dimensions and provide guidance for installation clearance. Drawings are not to scale.

Jackson Systems reserves the right to make product changes without notification or obligation.



5418 Elmwood Avenue, Indianapolis, IN 46203-6025 Toll Free: 888.652.9663 Fax: 317.227.1034 www.jacksonsystems.com