



### Features and Benefits

The Robertshaw® 620 Series Transformers are available in a wide variety of models from universal enclosed to single voltage open frame models.

- UL approved 1411
- Meets applicable NEMA standards
- Thermal fuse protection
- UL File No. E92807,

Robertshaw - *Simply the Right Choice™*

### Technical Specifications

Uni-Line® Part No.	Model	Rating (VA)	Primary Voltage (50/60 Hz)	Primary Lead Length	Secondary Voltage (50/60 Hz)	Secondary Lead Length
620-402	Universal Mounting - Foot, 4x4 Plate or Hub Mount	48 (Combined total output of all 3 secondaries.)	120/208/240	8"	2.5, 12, 24, or a combination of 2.5 & 24 or 12 & 24	8"
620-403	Universal Mounting - Foot, 4x4 Plate or Hub Mount	40	120	8"	24	8"
620-404	Universal Mounting - Foot, 4x4 Plate or Hub Mount	40	208/240	8"	24	8"
620-501	Universal Mounting - Foot, 4x4 Plate or Hub Mount	50	120/208/240	8"	28	Screw terminals
620-502	Universal Mounting - Foot, 4x4 Plate or Hub Mount	50	120/208/240	8"	24	8"
620-503	Universal Mounting - Foot, 4x4 Plate or Hub Mount	75	120/208/240/408	8"	24	8"
620-150	Foot Mounted	50	120/208/240	8"	28	Screw terminals
620-205	Foot Mounted	20	120	8"	24	8"
620-206	Foot Mounted	20	208/240	8"	24	8"
620-405	Foot Mounted	40	120	8"	24	8"
620-406	Foot Mounted	40	208/240	8"	24	8"
620-482	Foot Mounted	40	120/208/240	8"	24	8"
620-752	75 VA Foot Mounted	75	120/208/240	8"	24	8"
620-758	75 VA Foot Mounted	75	480	8"	24	8"
620-775	75 VA Foot Mounted	75	480	8"	24	8"
620-779	75 VA Foot Mounted	75	120/208/240/480	8"	24	8"
620-202	Plug-in	20	120	Plug-in	24	Screw terminals