



MECHANICAL THERMOSTATS





PS984-1R

Simply Reliable

Every job should be this easy. The PerfectSense™ PS900 Series Mechanical Thermostats are a simple two-piece design, so you save time at installation. The large display offers accurate room temperature measurement. Wall plates are available to mask any unsightly marks left by previous thermostats. Install it with confidence.

Features and Benefits

Accurate Room Temperature

Built-in thermometer accurately displays room temperature

Adjustable Heat Anticipator

Multiple anticipation settings for use on a wider range of heating equipment

No Sub-base Required

Simple base and cover design speeds installation. Base can be mounted on wall, freeing both hands for wiring

Mercury-Free

No leveling or special disposal required

J-Box Compatible

Meets code and speeds up installation

Positive Off Switch

Assured shutdown of HVAC system

Fixed Cooling Anticipation

Maintains optimal cooling comfort (PS984-1R, PS988-1R)

Dual Temperature Scale

Fahrenheit and Celsius scales displayed for flexible temperature setting (PS984-1R only)









MECHANICAL THERMOSTATS

| Technical Specifications | | |
|----------------------------------|--|--|
| PS984-1R | 24V AC, Cool Only | |
| PS986-1R | 24V AC, Heat Only | |
| PS988-1R | 24V AC, 1 Heat/ 1 Cool | |
| Electrical Rating | 24V AC (24-30V AC) and 250-750 mV 1.5 Amp maximum load (all terminals combined) | |
| Temperature Control Range | 50°F to 90°F (10°C to 30°C) | |
| Accuracy | ± 2°F | |
| Adjustable Heat Anticipation | 0.1 to 1.2 Amp | |
| Power Consumption | Less than 1 mA @ 24V AC | |
| Switch Action | Reed Switch | |
| Terminations | PS984-1R – Y, G, R PS986-1R – W, R PS988-1R – W, G, Y, Rc, Rh | |

Replacement Chart

White-Rodgers Company* 1E56

Honeywell, Inc.* T87

*Verify specific application requirements before substitution.

| PS984-1R | PS986-1R | PS988-1R |
|-----------------|---|--|
| 5" x 3" x 1.25" | 5" x 3" x 1.25" | 5" x 3" x 1.5" |
| 12 | 12 | 12 |
| 9.5" x 6" x 6" | 9.5" x 6" x 6" | 9.5" x 6" x 6" |
| .20 | .20 | .22 |
| 3.25 lbs. | 3.25 lbs. | 4.12 lbs. |
| 2016 | 2016 | 2016 |
| 44" x 42" x 40" | 44" x 42" x 40" | 44" x 42" x 40" |
| 42.78 | 42.78 | 42.78 |
| 586 lbs. | 586 lbs. | 1,080 lbs. |
| | 5" x 3" x 1.25" 12 9.5" x 6" x 6" .20 3.25 lbs. 2016 44" x 42" x 40" 42.78 | 5" x 3" x 1.25" 12 9.5" x 6" x 6" .20 3.25 lbs. 2016 44" x 42" x 40" 42.78 5" x 3" x 1.25" 12 9.5" x 6" x 6" .20 .20 44" x 42" x 40" 42.78 |