


SHM-Series Snap-Action Temperature Controls

The SHM-Series style temperature controls have a bi-metal disc that senses the temperature and quickly separates the contacts. This results in long life characteristics at loads up to 25 amps at 240 VAC. SHM-Series switches are single pole single throw 60T15 style (3/4") with manual-reset. These switches are designed to open on temperature rise. The surface mounting configuration positions the disc against the mounting surface to sense the actual surface temperature. Each switch comes with an adapter flange plate. For air-stream installation, simply attach the SHM control with the bi-metal protruding through the mounting surface. For surface installation, insert the two spacers between the screw holes in the flange, and the heating surface. Install the original screws and tighten securely.



| Part No. | Close | Open °F | |
|----------|------------|---------|--|
| SHM125 | Manual | 125 | |
| SHM130 | Manual | 130 | |
| SHM160 | Manual | 160 | |
| SHM170 | Manual | 170 | |
| SHM180 | Manual | 180 | |
| SHM200 | Manual | 200 | |
| SHM210 | Manual | 210 | |
| SHM290 | Manual 290 | | |
| SHM350 | Manual | 350 | |

Air Stream Mounting



| Contact Arrangement | FLA | LRA | Pilot Duty VA | Resistive Amps | Voltage AC |
|---------------------|-----|-----|---------------|----------------|------------|
| 1 & 3 SPST | 10 | 60 | 125 | 25 | 120 |
| 1 & 3 SPST | 5 | 30 | 125 | 25 | 240 |

800-333-9125 SUPCO.COM





