



VAV™

Diffusers

The Comfort System™ modulating VAV Diffuser is used to vary the supply air volume from a wall-mounted thermostat. This diffuser is designed to maintain coanda effect (draft free) of discharge air along the ceiling, providing a sustained discharge velocity throughout the volume range. Operating the diffuser from an individual wall-mounted thermostat enables the user to choose their desired comfort level. The wall-mounted thermostat will give closer temperature control and eliminate the need for a step ladder to adjust the setpoint of the diffuser.

COMFORT SYSTEM™

Features and Benefits:

- Wall-mounted thermostatic control within an individual zone
- Fully-modulating diffuser
- Powerful, low voltage floating-point actuator
- True variable air volume in heating and cooling modes
- Air volume ranges from 60 to 1,500 CFM
- Adjustable minimum and maximum air flows
- Suitable for lay-in ceilings
- Four-way discharge pattern
- Installation flexibility
- Increases comfort levels in individual zones without cycling equipment
- Can easily be converted into a full zoning system
- Custom colors available



Warranty: 5 years




Innovative Products

Free Same-Day Shipping

w: jacksonsystems.com

p: 888.652.9663



Specifications:

| | |
|-----------------------------|--|
| Construction | 18-gauge steel with baked enamel finish |
| Sizes | Diffuser sizes: 12" x 12" and 24" x 24" Neck sizes: 6", 8", 10", 12", 14" |
| Damper Actuator Type | 24VAC, 2VA, floating-point |
| Timing | 90 seconds |

Contractor Friendly

f: 317.227.1034

Strong Technical Support

e: info@jacksonsystems.com

JACKSON
SYSTEMS
Controls Done Right™