

## TWO-POSITION, 3-WIRE DAMPERS

The MD Series dampers are perfect for use with most zoning systems and recommended for use with all of our ESP zone panels. The MD Series dampers can be installed in any position. They are rated for duct systems less than 1.0" WC. The MD Series damper has a simple adjustment mechanism for setting the minimum and maximum position.

NO BYPASS REQUIRED!



EQUIPPED WITH  
**BELIMO**  
 ACTUATORS

### SPECIFICATIONS:

<b>Warranty</b>	5 years
<b>Construction</b>	Round: 24-gauge steel shell; Rectangular: extruded aluminum
<b>Sizes</b>	Round: 4" to 20"; Rectangular: 6" x 6" to 36" x 24" side-mount and bottom-mount
<b>Damper Actuator Type</b>	24VAC, 2.5VA, 18in lb, 3-wire power open/power close
<b>Timing</b>	60 seconds

### FEATURES AND BENEFITS:

- 24V, two-position, floating point actuator, 3-wire, power open/power close actuator
- Compatible with ESP panels to eliminate bypass
- Quiet operation
- Simple adjustment for setting the minimum position



5351 East Thompson Road Suite 142  
 Indianapolis, IN 46237  
 P: 888.359.0362  
 F: 317.489.5204

info@iOhvaccontrols.com  
 www.iOhvaccontrols.com

# DAMPER DIAGRAM

