

2-WIRE ROUND

The **D Series** dampers are galvanized steel, single-blade dampers with a 24 volt spring return actuator. These dampers are shipped complete and ready for installation. They are rated for duct systems with less than 1.0" WC. The D Series damper has a simple adjustment mechanism for setting the minimum position.



FEATURES AND BENEFITS:

- Compatible with most zone control panels
- Tight seal gasket
- 24V synchronous actuator
- Can be configured as PC/SO or PO/SC
- Quiet operation
- Simple adjustment mechanism for setting the minimum position

SPECIFICATIONS:

Warranty	5 years
Construction	24-gauge steel shell
Sizes	4", 5", 6", 7", 8", 9", 10", 12", 14", 16", 18", 20"
Damper Actuator Type	24VAC, 10VA, 2-wire spring return; Also available with 120VAC actuator



2-WIRE RECTANGULAR

The **HD Series** dampers are extruded aluminum parallel blade dampers with a 24 volt spring return actuator. The HD Series dampers can be installed in any position. They are rated for duct systems with less than 1.0" WC. The damper has a simple adjustment mechanism for setting the minimum position.

SPECIFICATIONS:

Warranty	5 years
Construction	Extruded aluminum
Sizes	6" x 6" to 36" x 24" side-mount or bottom-mount
Damper Actuator Type	24VAC, 10VA, 2-wire spring return; Also available with 120VAC actuator

FEATURES AND BENEFITS:

- Compatible with most zone control panels
- 24V synchronous motor
- Can be configured as PC/SO or PO/SC
- Quiet operation
- Simple adjustment mechanism for setting the minimum position
- Side or bottom mount



5351 East Thompson Road Suite 142
 Indianapolis, IN 46237
 P: 888.359.0362
 F: 317.489.5204

info@iOhvaccontrols.com
 www.iOhvaccontrols.com